

Cambridge Space Heaters Historical Comparison



	Model Number	Years Mfd.	Ratings (Maximum)					Dimensions										
			Input MBH	Blower CFM	Motor HP	Temp. Rise	Max. Disch.	Unit			Downturn Length	Dir. Elbows						
								Length	Width	Height		Opening	Qty.					
10" Blower	CH110 LC	87 - 89	400	2633	1	140°	140°	60"	25½"	25½"	13"	11" x 11"	2					
	CH110 HC	87 - 89	532	3500	2													
	CH110 LC	89 - 91	400	2304	1	160°	160°											
	CH110 HC	89 - 91	608	3500	2													
	C390	91 - 98	400	2304	1													
	C600	91 - 98	608	3500	2													
	S400	98 -	400	1850	1													
	S800	98 -	757	3500	3													
15" Blower	CH115 LC	87 - 89	600	3655	2	120°	120°	60"	35½"	25½"	13"	11" x 11"	3					
	CH115 HC	87 - 89	800	6150	5													
	CH115 HC	89 - 91	850	6150	5									140°				
	C900	91 - 98	900	5184	3	160°	160°							72"	42"	28"	15"	13" x 13"
	C1200	91 - 98	1200	6940	5													11" x 11"
	S950	03 -	950	4400	2													13" x 13"
	S1200	98 -	1200	5555	3													
	S1600	98 -	1499	6940	5													
20" Blower	CH120 LC	89 - 91	1500	8640	5	160°	160°	80"	47"	37½"	24¾"	11" x 11"	8					
	CH120 HC	89 - 91	2500	14400	15													
	C1900	91 -	1900	10945	7½													
	C2500	91 -	2500	14400	15								6					
	S1850	03 -	1850	8570	5													
	S2200	98 -	2200	10185	7½								8					
	S3200	98 -	3107	14380	15													